



## Get the right system and the best value for you.

When buying a pivot system don't play a numbers game. Make sure you are considering the numbers that make a difference; low maintenance cost, minimal downtime, the value of your time, efficient distribution of water on your fields, improved production, the savings of safety and more. These numbers will show you the "The Choice is Simple," T-L!

Then call our number, 1-800-330-4264, to find out how T-L hydrostatically powered pivot irrigation systems can be "Easier on You". Also visit our website at www.tlirr.com, or e-mail us at sales@ tlirr.com.

| Feature Specification            | T/L                                  | Their Best                | Their 2nd Best            |
|----------------------------------|--------------------------------------|---------------------------|---------------------------|
| Slope capability                 |                                      |                           |                           |
| 0" - 6" ridge                    | 158′ <b>20%</b>                      | 160′ 12%                  | 160′ 10%                  |
| Slope capability                 |                                      |                           |                           |
| 6" - 12" ridge                   | 177′8″ <b>15%</b>                    | 180′ 10%                  | 180′8%                    |
| Pipe sizes                       | 6 5/8", 8" & 10"                     | 6 5/8", 8", 8 5/8" & 10"  | 6 5/8" & 8"               |
| span weights - 6 5/8" pipe - wet | 158 ′ = 6200 = <b>39.24 / ft.</b>    | 160' = 6204 = 38.78 / ft. | 160' = 5892 = 36.83 / ft. |
| span weights - 6 5/8" pipe - wet | 187′ 6″ = 7300 = <b>38.93 / ft.</b>  | 180' = 6792 = 38.29 / ft. | 180' = 6408 = 35.60 / ft. |
| Corner                           | yes                                  | yes                       | no                        |
| Linear                           | yes                                  | yes                       | no                        |
| Towable                          | yes                                  | yes                       | no                        |
| Flange bolts                     | 5/8"                                 | 1/2"                      | 1/2"                      |
| Truss Rods                       | 3/4" 7/8" double tab<br>(3/4" bolts) | 3/4" 13/16" 7/8"          | 5/8"                      |
| Center Truss Angle               | 2 X 2 X 3/16"                        | 2 X 2 X 3/16"             | 2 X 2 X 1/8"              |
| Tower Legs                       | 3 X 3 X 1/4"                         | 3 X 3 X 1/4"              | 3 X 3 X 3/16"             |
| Span Wire                        | NO COPPERTHEFT - hydraulic std.      | 8 or 10 ga. X 11 cond.    | 10 or 12 ga. X 11 cond.   |
| Geardrive                        | Worm and Planetary                   | Worm                      | Worm                      |
| Planetary Geardrive warranty     | 8 yr / 24,000 hrs                    | NA                        | NA                        |
| Worm Geardrive warranty          | 8yr / 16,000 hrs                     | 8 yr / 8,000 hrs          | 8 yr / 8,000 hrs          |
| Alignment                        | hydraulic valve 8 year               | 2 yr - limited            | 2 yr - limited            |



**R&K PIVOTS** 300 DAV ROAD **PO BOX 643** RUSSELLVILLE, KY 42276

1-800-725-5986

www.randkpivots.com





151 East Hwy 6 & AB Road • P.O. Box 1047 Hastings, Nebraska 68902-1047 USA Phone: 1-800-330-4264 • Fax: 1-800-330-4268 Phone: (402) 462-4128 • Fax: (402) 462-4617 sales@tlirr.com • www.tlirr.com